

INTRINSICALLY SAFE



PHONE APP AVAILABLE

Recognize the potential for increased safety, significant productivity gains and time-savings with the new RMLD-CS. Remote detection allows utility services personnel and first responders to quickly scan an area for suspected gas leaks at a safe distance.

The HEATH Remote Methane Leak Detector - Complete Solution (RMLD-CS) is a highly advanced technology, capable of detecting methane leaks from a remote distance utilizing the same TDLAS (tunable diode laser absorption spectroscopy) technology as the current RMLD. This instrument eliminates the separate receiver and transceiver, combining them into one hand-held instrument that is lightweight, portable and field rugged. The RMLD-CS makes it possible to detect leaks without having to travel the entire length of the pipe line, thus creating safer surveys in areas that

may be difficult to reach such as busy roadways, yards with dogs, fenced off areas and other hard to access places. It operates under a variety of field conditions including a wide temperature range, light rain and fog. Its rugged design will stand up to normal field use and operating conditions and its sensitivity or range is not affected by reasonable amounts of dust on the instrument's window.

The RMLD-CS includes many new features including:

- Intrinsically safe
- Rechargeable/replaceable battery
- Dual battery charger
- Mobile App support
- Ergonomic housing
- Lightweight
- Graphical user interface
- Internal data logging
- WiFi
- GPS
- Bluetooth BLE
- Color camera and display



SPECIFICATIONS

General

Weight

3 lbs (approx.)

Carry Case Dimensions

21" x 17.5" x 9.5"

Display

3.5" color LCD, 320 x 240 resolution

Power

Battery

Removable

Rechargeable

Lithium-ion pack, 10.8 VDC at 3.2Ah



Battery Run Time

8 hours at 32° F (approx.)

Battery Charger

External, 110-240 VAC, 50/60 Hz Universal Dual Bay, Delivers 12W at 25°C per battery

Charge Time

2-3 hours full charge (approx.)

Detection/Measurement System

Detection Method

Tunable Diode Laser Absorption Spectroscopy (TDLAS)

Detection Distance

100 ft (30m) nominal - may vary due to background type and conditions

Measurement Range

0 to 50K PPM-M

Sensitivity

5 PPM-M at distances from 0 to 100 ft (30m)

Beam Size

Conical in shape with a 22" diameter at 100 ft (55cm at 30m)

Lasers

IR Laser

Class I

Green Spotter

Class 2(II) <5mW @ 510-530 nm
Spot size is 7mm at 15M

Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007

Laser Eye Safety Warning

Do not stare into beam or view directly with optical instrument



Color Camera

Aperture

f/2.6

FOV

94DEG (at 6.0mm image circle)

GNSS Compatibility

GPS

GLONASS

Beidou

Galileo

Communication

USB Dual Mode – flash drive and communications

USB Port Max Rating: Um = 5V, In = 5 A

Bluetooth 4.2 BLE

WiFi b/g

Alarms

Digital Methane Detection (DMD)

Audible tone and visual alerts when detection threshold exceeded

Adjustable Detection Alarm Level

1 to 9990 PPM-M

Real Time (RT)

Continuous beep rate relative to concentration from 10-1000 PPM-M

System Fault & Warnings

Audible alarm and visual indication on the display

Testing

Built-In Self-Test

Verifies operation and adjusts laser wavelength for maximum sensitivity

Test Gas Cell

Integrated within carrying case

Operating Conditions

Operating Temperature

0° to +122° F (-17° to 50° C)

Humidity

5 to 95% RH, non-condensing

Altitude

Up to 2000M

Environment of Use

Pollution degree 2 or better
Outdoor use

Regulatory

Ingress Protection

IP54 (water splash and dust resistant)

Compliance

EMC (EN61000-6-2, EN6100-6-4)



Radio Equipment Directive

(2014/53/EU)

ETSI EN 301 489-1 v2.2.0

EN 61326-1:2013

47 CFR Part 15 & ICES-003

Ordinary Location Safety

UL 61010-1

CAN/CSA-C22.2 No 61010-1-12

Hazardous Location Safety

Class I, Zone 2, AEx ic op is IIA T4 Gc

Class I, Division 2, Group D Intrinsically Safe

Ordering Information

RMLD-CS - HPN 105301

Includes carry strap, case, battery charger, power supply, USB cable, one battery pack, gas calibration test cell

IS Battery Pack - HPN 105727

Li-ion replacement battery

Battery Charger Base - HPN 105358

Battery Charger Cable - HPN 105359

Charges two batteries at one time



Your Safety...Our Commitment

9030 Monroe Road

Houston, TX 77061

Ph: 713-844-1300

info@heathus.com

www.heathus.com